

## FEATURES

- Meets or exceeds the following industry standards:
- Mercon® V (approved)
- Voith extended drain
- ZF (TE-ML.14.B)
- Toyota T-IV, Type WS, and previous
- Mitsubishi Diamond SP III, SP II
- Allison C-4
- JASO 1A, 2A
- Audi, VW, Mercedes, BMW
- Caterpillar TO-2
- ATF +4, ATF +3 capable
- Suitable for use where Dexron® IIIH, IIIG, IIE, or II is recommended. Not suitable where Dexron® VI is required

## BENEFITS

- Maximum value service life - up to 100,000 miles or 50,000 miles in severe duty as recommended by OEM's
- Exceptional low temperature fluidity
- Excellent resistance to degradation due to heat and oxidation
- Eliminates slippage and shudder
- Extends integrity and operational life of critical components

Q.A.P MULTI-VEHICLE ATF is a premium synthetic blend transmission fluid designed to provide unparalleled severe duty operating performance in automatic transmissions. It has enhanced resistance to oxidation and prevents the formation of gum or varnish in the transmission due to high temperature instability.


Q.A.P MULTI-VEHICLE ATF offers excellent fluidity at low temperature allowing better cold lubrication and faster flow rates reducing warm up time. It has very good thermal stability, protects better and longer to reduce wear and extend the transmission life. It has a very good anti-corrosive and anti-foam characteristic. Its synthetic low friction properties ensure less vibration, slippage and shutter, even during rapid acceleration.

Q.A.P MULTI-VEHICLE ATF is Mercon® V approved. It is also suitable for use in transmissions requiring ATF +4, ATF +3, Voith, ZF, and where Dexron III-H, III-G, & II are required.

Q.A.P MULTI-VEHICLE ATF may also be used as a hydraulic or power steering fluid where use of an ATF in these applications is permitted by the manufacturer.

Q.A.P MULTI-VEHICLE ATF is not recommended for applications requiring Type F or DEXRON® VI. Where DEXRON VI is required, use Q.A.P DEXRON® VI ATF.

## AVAILABLE SIZES





# MULTI VEHICLE ATF

## TYPICAL PERFORMANCE RESULTS

COLOUR	Red
DENSITY, KG/L @ 15°C(60°F) D-4052	0.854
VISCOSITY D-445 cSt @ 40°C (SUS @ 100°F)	34.0
cSt @ 100°C (SUS @ 210°F)	7.6
VISCOSITY INDEX D-2270	204
BROOKFIELD VISC. D-2983 cP @ -40°C (-40°F)	9580
POUR POINT °C (°F) D-97	-48
FLASH POINT °C (°F) D-92	214

## AVAILABLE SIZES & CODES

	946ml. (1 US qt)	3.78L (1 US Gal)	18.9L (5.0 US Gal)	205L (54.2 US Gal)	210L (55.5 US Gal)
Q.A.P M-V ATF	QDEXRONMULTI-1 FX0001815				

**Available Exclusively at  
Bestbuy Distributor Locations**

**Quality  
AUTOMOTIVE  
Products™**