

# Bosch ESI6-32N

The next generation brake fluid



Modern brake systems, such as those featuring ABS and ESP®, are designed for improved performance to safely stop vehicles. With improved performance comes a higher load on the braking systems. These systems require a brake fluid with a high wet boiling point, low viscosity, and high lubricity.

As a vehicle system developer and the first to market ABS and inventor of ESP®, Bosch understands the need for a high quality brake fluid.

Bosch ESI6-32N is the next generation brake fluid. It exceeds all current DOT standard requirements (FMVSS 116).

**Best value on the shelf:**

- ▶ First to simultaneously combine both low viscosity and high wet boiling point at its operation
- ▶ Longer lasting: 100% longer than DOT 3, 50% longer than DOT 4, and 10% longer than DOT 5.1 (with 30% lower viscosity)
- ▶ ESI coverage includes the majority of all brake systems launched since 1990; Use with DOT 3, DOT 4, or DOT 5.1; Coverage excludes DOT 5 silicone based brake fluid which is limited to military and racing applications
- ▶ Excellent lubricity properties to prevent wear of components in the brake system and reduce noise

ESI6-32N contributes to the high performance and service life of modern brake systems with its high dynamic properties. For over two years, it has undergone sophisticated testing geared towards new versions of ABS and ESP® systems in our Bosch development center in Abstatt, Germany.



ESI6-32N is subject to chemical testing in the development center laboratory.



High-tech laboratory continuous-operation test benches

ESI6-32N brake fluid has been subject to intense testing of both system pressure build-up and wear and noise at extreme temperatures.



**ClearWeld™ Epoxy**  
50240CAN  
4oz/each



**O'KEEFFE'S Gift Pack**  
100919  
Includes:

- **Working Hands** Hand Cream
- For **Healthy Feet** Foot Cream
- **Lip Repair** Cooling Relief

**March 2020**



**Leather**  
U1P-10290



**Black Ice**  
U1P-10155



**Strawberry**  
U1P-10312



**New Car Scent**  
U1P-10189



**Vanillaroma**  
U1P-10105



**SCOTT® Jumbo Bathroom Tissue**  
07805



**SCOTT® Towels**  
01010



**SCOTT® Bathroom Tissue, 2-ply**  
48040

**Battery Nut Pliers**  
55240



**Heater Hose Disconnect**  
**GM 3/4"**  
39190



**Timing Tool For Ford**  
**3.5L Turbo**  
37350



Disclaimer: Products may not be available at all locations and may not be exactly as shown. Minimum purchase may be required. Flyer pricing is not guaranteed. Price and availability may vary from store to store. Please inquire at your local Bestbuy Jobber.





**Mobil1 Motor Oil**

**5W30 Synthetic**  
MOBIL5W30

**5W20 Synthetic**  
MOBIL5W20

**Advanced Fuel Economy**  
MOBIL0W20

**European Car Formula**  
MOBIL0W40

**10W30 Synthetic**  
MOBIL10W30



Sold by case of 6



**WD-40® Multi-Use Product**  
01111 - 311g



**2000 Flushes Automatic Toilet Bowl Cleaner**  
90616 - 35g Chlorine



**PERFECT STEEL™**  
0.25 oz. segments  
Dimensions : Low profile,  
0.1875" height, 1" width



**QuikStik®**  
200576FE - 3 oz. per strip  
48 strips; 576 segments

**QuikRoll®**  
200576FER - 11lb roll, 704 segments

**PERFECT STEEL™  
CLIP-ON WHEEL WEIGHTS**

Featuring a patented clip design called the SecureClip™ and the Perfect "P" as a mark for quality.

**PFE-Series**

The most common weight for steel wheels. Will fit standard-width rim flange thickness passenger car steel wheels with 13"-17" wheel size.

**Fits** Standard-width rim flange thickness passenger car steel wheels with 13"-17" wheel size.

**Available Sizes** 0.25 oz. - 2.50 oz.



**For Steel Wheels** **5-Year Coating**  
 **Ounces Only**

| Part#  | Size     | Pcs. / box | Part#  | Size     | Pcs. / box |
|--------|----------|------------|--------|----------|------------|
| P025FE | 0.25 oz. | 25         | P100FE | 1.00 oz. | 25         |
| P050FE | 0.50 oz. | 25         | P125FE | 1.25 oz. | 25         |
| P075FE | 0.75 oz. | 25         | P150FE | 1.50 oz. | 25         |
|        |          |            | P175FE | 1.75 oz. | 25         |



**Permatex® Blue Medium Strength Threadlocker**  
24240 - 36ml Carded Bottle  
Medium strength, general purpose threadlocker.



**Permatex® Red high Strength Threadlocker**  
26240 - 36ml Carded Bottle  
High strength threadlocker.



**Permatex® Dielectric Tune-up Grease**  
22064 - 85g Carded Tube  
Necessary for an effective tune-up on high energy ignition services. Prevents voltage leak around any electrical connection.



**New 35g GEL Threadlockers**  
  
24235 - Medium Strength Threadlocker BLUE Gel  
  
27135 - High Strength Threadlocker RED Gel



**Easy-Load Gasket Kits**  
Includes:  
2 x 147mL Cartridges  
1 x Easy-Load Cartridge Gun



**Ultra Black**  
99657



**Ultra Grey**  
99658



**Ultra Copper**  
99659

**SNAP-IN VALVES**  
High-quality rubber snap-in valves available from the leader in wheel balance weight.

**Standard valve**  
TR418  
Rim hole: 0.453"  
Length: 2"  
Pressure: 65PSI

