

Prices valid January 1st - February 28th, 2023

Dorman Universal Seat Heater

628-040

Can be installed on any vehicle!



Universal Reservoir 603-001





Universal Oil Drain Plug And Gasket Tech Tray 030-502



O-Ring Assortment 80000



Fuel Injector O-Ring Assortment 90100 30 Piece



Fastener Tech Tray 030-731 - HONDA 030-734 - GM



Universal Washer Nozzle Kit 47237 Rivet Gun Window Regulator Installation Tool 743-100



Windshield Wiper Arm Tool 49023



BOSCH SNOW DRIVER™

Tested to perform at -29°C

| • | |
|------|------|
| 13SD | 20SD |
| 15SD | 21SD |
| 16SD | 22SD |
| 17SD | |
| 18SD | 20SD |
| 19SD | 21SD |
| | 22SD |
| | 2230 |



Hub Remover 40100



Gasket Separator 50210



Spill-Free DEF Kit with GM Adapter 24210



Curved Hose Clamp Pliers 17460



Flexible Hose Clamp Tool





Carbide Scraper 81990 - 8" x 1^{1/4}"



Parts Brush™ Atlasta® Soft Brush 89510



Disconnect Pliers, 45 Degree37140





Heavy Duty Push Button/Horn 9452-11



Metal Bat Handle Switch SPST 9432-11 - 12V 20A



Metal Bat Handle Switch SPST 9435BP



Black Dual Wall Heat Shrink Tube 6 X 6" BAG



PICO

8329A

Inside diameter: 1/8" (3.2mm)

8330A

Inside diameter: 3/16" (4.8mm)

8331A

Inside diameter: 1/4" (6.4 mm)



Includes inside diameters 1/8", 3/16", 1/4", 3/8", 1/2", 3/4"

67-91 3:1 DUAL

56-91 2:1 SINGLE



RTV Silicone Adhesive Sealant BLACK - 300mL Cartridge



Heavy Duty Spray Adhesive 27829



Super Glue Instant Adhesive 49512 - 28g Carded Bottle





Blue Medium Strength 24240 36ml Carded Bottle



Red **High Strength** 26240 36ml Carded Bottle



Orange Hybrid Strength 25236 36ml Carded Tube



Liquid Copper Block Seal Intake & Radiator Stop Leak 31109 510g



Head Gasket Fix 31111 680g

RISLONE



Hydraulic Seal 32820



Cooling System Repair 31150 - 500ml



Fuel, Exhaust & **Emissions System** Cleaner 34720 - 500ml



Heavy Duty Oil Stabilizer 20001



Air Tool Oil 1001-16 16oz




1001-4 4oz



OMPRESSOR OIL

Compressor Oil 1002-32 32oz







PIVOT Super Bright Strip Array Technology

- Strip array led face worklight
- 5 Led top flashlight
- 360 Swivel hook
- Magnetic base
- Magnetic back
- 3 AA batteries included



Chrome Tri-Tap Cord Reel 222308

- Tri-tap outlet
- 13 amp circuit breaker
- 30 ft. / 9.2m SJTW 14/3 cable







PURIFIER™

170AIR

- Fresh Air Ozone Machine
- Incorporates the latest in ozone purification technology
- Eliminates mold, mildew, & bacteria from cabin interiors & rooms
- Removes even the most offensive & stubborn odors such as tobacco smoke
- Portable design AC (100-240 V) & DC power
- 10 hour programmable timer with LCD



Fuel Line Clip Assortment 0289 31 pcs



K100S 2 Year Fuel **Stabilizer Treatment**

K100S32

2 year Fuel Stabilizer treatment for all Gasoline Engines.



Fuel Injection Hose Clamps

FI4 1/4"

FI6 5/16

FI8 3/8







Black Fuel Rated Nylon Tubing Coils

2962-25 5/16 x 25'

2963-25 10 mm x 25'

3/8 x 25' 2998-25

Cupro Nickel Brake Line Coils

CN3 3/16 x 25'

CN4 1/4 x 25'

CN5 5/16 x 25'

RUST'S WORST ENEMY

POWERFUL RUST & CORROSION PROTECTION EXCELLENT VEHICLE UNDERCOATING SUPERIOR LUBRICANT • LONG-TERM PENETRANT ENVIRONMENTALLY FRIENDLIER • SOLVENT FREE • NON-TOXIC

THE MOST UNIVERSAL PRODUCT YOU WILL EVER USE!!

"WOOL WAX
FORMULA"

| NLS Products Stock # | Size | |
|----------------------|--------|--|
| 6300 | 333 g | |
| 6400 | 3.78 L | |
| 6500 | 18.9 L | |





AUTO • TRUCK • FARM • HOME • MARINE • FORESTRY • MINING • INDUSTRIAL • RVs BUSES • TRAILERS • CHAINS • ATVs • AIRCRAFT • MILITARY • SALT TRUCKS • CABLES BATTERY TERMINALS • TOOLS • FERTILIZER SPREADER • ELECTRICAL CONNECTORS

DECEMBER 1

- NOT WATER SOLUBLE
- REPELS & RESISTS WATER WASHOUT
- WILL NOT DRY OUT OR EVAPORATE
- APPLY OVER DRY OR DAMP SURFACES
- REDUCES STRESS CORROSION

- PREVENTS ICE & SNOW FROM BUILDING UP ON MOVING PARTS
- WORKS IN SUB-ZERO WEATHER -46°C (-50°F) TO 177°C (350°F)
- NON-CONDUCTOR OF ELECTRICITY
- WILL NOT CAUSE STATIC ELECTRICITY
- SOLVENT, TEFLON & SILICONE FREE

NATURE GIVEN MATERIAL

FLUID FILM UTILIZES THE UNIQUE MOLECULAR ACTION DERIVED FROM WOOL-WAX, A NATURE GIVEN MATERIAL (Lanolin) & other corrosion inhibiting ingredients. One of the best lubricants & corrosion control agents found in nature today. In use for over 60 years in the Highly Corrosive Marine Environments of ships & off-shore drilling rigs.

LONG-TERM PROTECTIVE PROPERTIES START WORKING IMMEDIATELY

FLUID FILM - developed & perfected as an unparalleled Rust & Corrosion Control System. Non-drying properties for Superior Lubrication & is a Long Term Penetrant. Once in place, stays put, forming a continuous, durable, ALWAYS ACTIVE protective barrier. Will not harm most paint or plastic surfaces. Will not harm oil resistant seals. Take care when applying near rubber. Overspray must be wiped with a clean, dry cloth as it may cause swelling. Repels & resists water washout.

Displaces moisture. Excellent waterproofing with "NO DRIP" bonding properties. FLUID FILM penetrates right through rust, stopping all metal deterioration on contact. Migrates to inaccessible areas by capillary action. Impregnates the pores of exposed metal, keeping moisture & oxygen out.

Certified Salt Spray Test - 1800 Hrs. U.S. Navy & 10 Military GSA National Stock Numbers (NSN).


TERMINATES BOTH NATURAL & INDUSTRIAL ATMOSPHERIC CORROSION

Eliminates the destructive corrosive effects of harsh minerals & chemicals such as salt, salt air, brine solution, acid, calcium, sodium chloride, fertilizers, herbicides & pesticides. FLUID FILM prevents steel from rusting; aluminum, magnesium, copper, tin, bronze & zinc from oxidizing; chrome & brass from pitting.

VEHICLE UNDERCOATING APPLICATION INSTRUCTIONS

Recommended Sprayers: # L015-203 - Hand-Filled Container, # L033-207 - Pail Pump Unit, # L033-208 - Drum Pump Unit, # L090-90 Drum Lid SHAKE WELL BEFORE USING. (Apply Sparingly) Apply FLUID FILM "NAS" by brush, roller, dipping or pressurized sprayer at 60 to 80 psi, (at the sprayer) with a spray nozzle orifice of 40-50 thou. KEEP CONTAINER TIGHTLY CLOSED.

FLUID FILM UNDERCOATING: Give the vehicle's undercarriage a blast of water to clean off any excess dirt & let the heavy water drip off for 5 minutes. Apply to the panels and doors as normal. Apply FLUID FILM right over the damp metal. If dripping occurs then you are over-applying the product. If previously undercoated, please check for product compatibility.





Bestbuy Pro Synthetic 5W-40 CK-4 FX0004030

BESTBUY



Q.A.P Synthetic LV **Multi-Vehicle ATF** FX0002415 946ml



2 Stroke Synthetic Oil F0070315 946ml







Original **Protectant Wipes** 10859 25 wipes



Cleaning Wipes 10869 25 wipes



Glass Wipes 10850 20 wipes



Leather Wipes 10856 20 wipes



Protectant Sponge 19077



Cleaning Sponge 19078



Original Protectant 78021 473ml



WYPALL* SHOPPRO* X80 **Shop Towels** 41041



Cottonelle® Professional Standard Roll Toilet Paper 17713





WYPALL® GENERAL CLEAN L20 Medium Cleaning Cloths 34607



3-Layer Breathing Masks Box of 50 MNS01



15'x1" General Purpose Ratchet w/Padded Handle SL91 - 4 pack



Strap Assembly - 1" Ratchet Buckle-10' w/vinyl S-Hooks 95002 - 2 pack



95005 - 4 pack

Natural Rubber Tarp Tie Premium Brand

52215C 15"

52221C 21"

52231C 31"





Gorilla Tape To-Go 6101002 - 30 feet



Cleaner/Degreaser

25416 -990ml Uses: Automobiles, garages, marine, RVs, ATVs, motorcycles, household





Mounting Tape 6069301 24 1x1 inch squares



BESTBUY

Hard Surface Disinfectant 20201 1L One step all purpose cleaner



All Weather Seal 9132-16 - 1 pint



- It blends with your existing Antifreeze forming a microemulsion
- It only works where the leak is. No fear of plugging heater cores, etc.
- It can be used as a preventative to keep vehicles in service



LED HEADLIGHTS

LED REPLACEMENT BULBS
FOR HALOGEN HEADLIGHTS AND FOG LIGHTS



ZEVO® LED HEADLIGHTS





SYLVANIA



AVAILABLE PART NUMBERS

9145 | H8 | 9003 | 9006 | H11 | H7 | 9005 | 9007 | H13

SYLVANIA LED HEADLIGHTS



2 Year Warranty



6000K cool white light



5 minute install



Turbo cooled at 10,000 RPM to maximize LED Life

AVAILABLE PART NUMBERS

9003 | 9005 | 9006 | H1 | H7 | H9 | H11

*See Package for details